

METAL COMPONENTS

Sheet metal clips

0.50 mm steel clips for joining PET and PP strap.

The supplied catalogue specifies open 0.50 mm steel clips for matched PET and PP strapping systems. Confirm strap grade, clip profile and crimping-tool suitability before ordering.



Specifications

STRAP WIDTHS	12–19 mm · 3 sizes
SHEET THICKNESS	0.50 mm
MATERIAL	Steel sheet
FINISH	On request
COMPATIBLE STRAP	PET / PP subject to clip, strap and tool validation
PACKING	Cartons of 1,000 / 800 / 500 pieces
STRENGTH	On request

Sizes and carton data

PART NO.	STRAP WIDTH	SHEET THICKNESS	PCS / CARTON	NET WEIGHT / CARTON	CARTON (CM)	CARTONS / PALLET
YK-SC-12 On request	12 mm · 1/2 in	0.50 mm	1,000	3 kg	On request	300
YK-SC-16 On request	16 mm · 5/8 in	0.50 mm	800	3 kg	On request	300
YK-SC-19 On request	19 mm · 3/4 in	0.50 mm	500	3 kg	On request	300

- 12 mm clips for 12 mm strap, 16 mm for 16 mm, 19 mm for 19 mm. Packed 1,000, 800 and 500 clips per carton respectively.
- Strap width is the nominal width of the strap this product fits, not the product's outside size.

Applications

Cartons and light pallets

12 and 16 mm clips with 12 and 16 mm PET strap.

Heavy pallets with PET strap

16 and 19 mm clips with 16 and 19 mm PET strap.

Bundles closed with a crimping tool

For a validated PET or PP strap, clip and tool combination.

Pairs with

PET strap

12–19 mm

Embossed polyester strap in 12–19 mm widths, on request.

Use with green PET strap in the same width. One clip per joint.

How it is used

- 1** **Overlap**
Overlap the two strap ends inside the clip.
- 2** **Tension**
Pull the strap tight with a tensioner.
- 3** **Crimp**
Close the clip with a crimping tool to lock the joint.

Notes

- Typical values per carton.
- Application examples are starting points, not load ratings. Match strap grade, accessory geometry and finish, tool and load conditions, then validate complete-joint performance before use. Availability is on request.
- Finish: on request.
- A matched crimping tool is needed to close the joint.
- Published specifications are catalogue references. Exact dimensions, system suitability and availability are reviewed with your quotation.
- Generated from the YAKU product data. Unknown values read “On request”.

Contact

Mobile / WhatsApp

+971 56 176 8591